

Environmental Data Sheet

ECOSYS M3655idn/A

Environmental Management	This device is manufactured in production facilities that work with an environmental management system in accordance with ISO 14001.		
Power Consumption Heat Emission	Maximum (at switch on, full options): 1307 W 4705 kJ/h Printing: 711 W 2560 kJ/h Ready: 54 W 194 kJ/h Low power mode: 30 W 108 kJ/h Sleep-mode: 0.5 W 1.8 kJ/h Off-mode: 0.09 W 0.3 kJ/h		
Typical Power Consumption (TEC) (according to ENERGY STAR 3.0)	0.74 kWh/week (7520 pages/week)		
Installation Notes	The unit should be placed in a way, that there is adequately space for operation and maintenance on both sides, as well as in front and behind the system. Provide adequate ventilation. Do not set up the unit in dusty rooms, and protect against ammonia vapours. Please follow the instructions in the user manual.		
Humidity	15% – 80%		
Room Temperature	10°C – 32.5°C		
Noise Emission (according to ISO 7779)	Operation	Ready	Quiet-Mode
	Surface sound pressure level (measurement in 1m distance, average of single measurements) [dB(A) L _{pA}]		
	54.7	25.8	51.5
	Operator position [dB(A) L _{pA}]		
	60.5	29.3	
	Sound power level (DE-UZ 219) [dB(A) L _{WA} d]		
	71.1		
Light Source	Exposure drum: Laser		
Emission	According to DE-UZ 219		
	TVOC (Operation):	4.56 mg/h	
	TVOC (Ready):	0.114 mg/h	
	Benzene:	< limit of detection	
	Styrene:	0.06 mg/h	
	Ozone:	< limit of detection	
	Dust:	0.27 mg/h	
ECOLabel	Exposure drum: Laser Product related environmental labels in Germany/Austria: Blue Angel DE-UZ 219 Status: Awarded List of certified KYOCERA products can be found here: https://www.blauer-engel.de/en/products/company/kyocera-document-solutions-deutschland-gmbh-only-de-at		
	Other countries: Please refer to the local country information.		

effective 09/2022 – Errors and omissions excepted